

# IKA

designed for scientists



## KS 130 basic

/// Data Sheet

Small, quiet orbital shaker ensures long life with ideal swivel motion, for a maximum shaking weight of 2 kg.

- Electronic adjustment of speed and timer
- LED display for speed and time adjustment
- Wide range of attachment combinations makes it possible to use almost all shapes and sizes of vessels
- Attachments are not included, please order separately

[www.ika.com](http://www.ika.com)

Subject to technical changes

 IKAworldwide

 IKAworldwide /// #lookattheblue

 @IKAworldwide



designed for scientists

### Technical Data

Type of movement	orbital
Shaking stroke [mm]	4
Permissible shaking weight (incl. attachment) [kg]	2.0
Motor rating input [W]	45
Motor rating output [W]	10
Permissible ON time [%]	100
Speed min (adjustable) [rpm]	80
Speed range [rpm]	0 - 800
Speed display	LED line
Timer	yes
Timer display	LED line
Time setting range [min]	5 - 50
Operating mode	timer and continuous operation
Dimensions (W x H x D) [mm]	270 x 98 x 316
Weight [kg]	8.8
Permissible ambient temperature [°C]	5 - 50
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 21
Voltage [V]	220 - 240
Frequency [Hz]	50/60
Power input [W]	45

